

FS-1118MFP

A4 MONOCHROME MULTIFUNCTIONAL

► print ► copy ► scan ► fax

TIME TO SHARE WITH A SMALL MULTIFUNCTIONAL THAT'S BIG ON PERFORMANCE.

This compact network multifunction device is top of the class in reliability and efficiency. Our unique long-life ECOSYS technology provides cost-efficient productivity in a multitasking environment. The perfect choice when you want print and copy functions as well as the ability to scan in colour and send faxes.

- 18 pages per minute with 1,200 dpi quality
- 96MB memory for advanced functions (max. 320MB)
- Standard network interface
- Full colour scanning
- Long-life components

Product depicted includes optional extras

300-sheet paper capacity as standard. To increase productivity, upgrade to 550 sheets input capacity.



The optional document processor allows you to scan, copy or fax up to 50 pages of originals.



ECOSYS

 **KYOCERA**

FS-1118MFP

A4 MONOCHROME MULTIFUNCTIONAL



ECOSYS devices are designed to minimise both direct costs and indirect costs such as maintenance, administration and consumables. The cartridge-free system requires only the toner to be replaced. The modular design concept allows you to add workflow enhancing functions and a wide variety of paper handling capabilities as required. Integrated system software provides long-term cross-network compatibility. Kyocera's long-life components cost you and the environment less.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speed: Max. 18 pages A4 per minute
Resolution: 600 x 600 dpi, 256 greyscales (scan/copy), 1200 dpi quality (1,800 x 600 dpi) with KIR2 (print)
Time to first copy: 9.5 seconds or less
Time to first print: 8.0 seconds or less
Warm-up time: 20 seconds or less
Duty cycle: Max. 10,000 pages per month, max. average 2,800 pages per month
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Copying/Printing: 409 W, Stand-by: 76 W, Power-Saving (ECOpower): 40 W
Noise (ISO 7779): Copying/Printing: 65 dB(A), Stand-by: 43 dB(A)
Dimensions (W x D x H): 496 x 421 x 385 mm
Weight: Main unit: Approx. 14.5 kg
Certifications: TÜV/GS, CE
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 250-sheet universal paper feeder, 60-105g/m², A4, B5, A5, A6, Letter, Legal, Folio
50-sheet multi-purpose tray, 60-163g/m², A4, B5, A5, A6, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm), envelopes
Max. input capacity with options: 550 sheets
Output capacity: 150 sheets face-down, 30 sheets face-up

COPY FUNCTIONS

Max. original size: A4, Folio
Continuous copying: 1-999
Memory capacity: Standard 96MB, max. 320MB, 1 additional DIMM slot (64, 128, 256MB)
Zoom range: 50-200% in 1% steps
Preset magnification ratios: 6R / 4E
Digital features: Scan-once-print-many, electronic sort, auto start, auto cassette change, density adjustment, paper size selection, layout mode (2in1, 4in1), program, interrupt, ECOcopy mode, job reservation, department code (20 codes)
Exposure mode: Auto, manual: 7 steps
Image adjustments: Text + photo, text, photo

Your Kyocera Business Partner:

PRINT FUNCTIONS

Processor: PowerPC 750Cxr / 300MHz
Memory: Standard 96MB (64MB + 32MB DIMM), max. 320MB (1 additional DIMM slot for 64, 128, 256MB)
Emulations: PCL6/PCL5e incl. P.JL, KPDL 3 (PostScript 3 compatible) with automatic emulation sensing (AES), PDF direct printing, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts accessible in all emulations, 1 bitmap font (PCL, KPDL2), 45 types of one-dimensional barcodes, plus two-dimensional barcode (PDF-417)
Features: IPP printing, E-mail printing

INTERFACES

Standard interface: High-speed bi-directional parallel (IEEE 1284), USB 2.0 (Hi-Speed), Fast Ethernet 10/100Base-TX standard
Multiple interface connection (MIC): Allows simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.

COLOUR SCAN FUNCTIONS

Functionality: Scan-to-Email, Scan-to-FTP, Scan-to-SMB, TWIN, LDAP
Scan speed: Max. 18 originals per minute (600 dpi / A4, b/w)
Scan resolution: 600, 400, 300, 200 dpi (256 greyscales)
Maximum scan size: A4, Folio
Original recognition: Text, photo, text + photo OCR
Interface: 10/100Base-TX, USB 2.0 (TWIN only)
Network protocol: TCP/IP
File types: TIFF (b/w only), PDF, JPEG (colour only)
Compression format: MMR/JPEG

FAX FUNCTIONS (OPTIONAL)*

Compatibility: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: 3 seconds or less (JBIG)
Scanning speed: 2.5 seconds
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm
Maximum original size: A4, Folio
Compression method: JBIG, MMR, MR, MH
Memory reception: 256 sheets or more with ITU-T No. 1 chart
Fax features: Network faxing, confidential, polling transmission and reception, broadcast, sub-code, document box, remote diagnosis

*Requires optional document processor DP-100

OPTIONS

Fax system (K)

Paper handling
DP-100 Document processor: 50 sheets, 50-120g/m², A5R-A4R, Folio
PF-17 Paper feeder: 250 sheets, 60-105g/m², A4, B5, A5, Letter, Legal, Custom (148 x 210 mm to 216 x 297 mm)
CB-100 Cabinet: Wooden desk with storage capacity, including castors (wheels)

Memory
1 DIMM slot (64, 128, 256MB)

CONSUMABLES

TK-18 Toner-kit: Microfine toner for 7,200 pages in accordance with ISO 10561B

Capacity of starter toner for 3,600 pages in accordance with ISO 10561B

WARRANTY

2-year warranty as standard. Kyocera guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

KYO LIFE KYOlife 3-year on-site warranty for printer and options.



Select your options to suit your needs:

Document processor (DP-100)

Paper feeder (PF-17)

Cabinet (CB-100)



Product depicted includes optional extras

KYOCERA MITA Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com
KYOCERA MITA Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

