

FS-C1020MFP

► print ► copy ► scan ► fax

THE ECONOMICAL COLOUR PROFESSIONAL.

The colour multifunctional device FS-C1020MFP prints out up to 20 pages per minute in b/w and colour. Compact and user-friendly, it provides fast and easy access to all the print, copy, scan and fax functions. And with its standard network interface, it is the perfect network device for your office or work group.

- Up to 20 pages per minute in b/w and colour
- Time of first print 14 seconds or less
- Standard fax functionality
- Standard duplex unit for cost-saving double-sided printing
- Standard 35-sheet document processor
- Standard network interface
- Optional paper feeder for up to 750 sheets
- Very compact and user-friendly design



Security functionality for printing confidential documents that can only be printed out with input of a password on the operation panel.

Innovative design makes this multifunctional easy to operate. Simplified top access ensures fast worry-free toner replacement.



FS-C1020MFP

COLOUR MULTIFUNCTIONAL FOR A4 FORMAT

General

Technology

Laser colour

Engine speed

Up to 20 pages per minute in A4, b/w and colour

Resolution

600 dpi (copy/print), 1,200x600 dpi, 2,400x600 dpi (print)

Memory

Standard 128 MB, optional 256 MB (1 additional DIMM slot)

Warm-up time

Approx. 48 seconds or less from power on

Dimensions (W x D x H)

420 mm x 493 mm x 476 mm

Weight

Approx. 30 kg

Power source

220/240 V, 50/60 Hz

Power consumption

Max. power consumption: 1,300 W

Sleep mode: 25 W

Noise

Ready mode: 34 dB(A)

Copy/print mode: 58 dB(A)

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity

250-sheet universal paper cassette, 60–160 g/m²;

from 90 x 148 to 216 x 356 mm;

1-sheet bypass tray, 60–160 g/m²;

500-sheet optional paper feeder, 60–105 g/m²;

Max. input capacity incl. options: 751 sheets

Duplex unit

Duplex as standard supports 60–90 g/m²

Document processor

Up to 35 sheets, 52–105 g/m², from 140 to 216 mm width;

from 140 to 356 mm length

Output capacity

150 sheet face-down

Print functions

Controller

ARM/400 MHz

Standard interfaces

USB 2.0, Ethernet 10/100Base-TX

First printout time

14 seconds

Operating systems

Windows® 2000/XP/Server 2003/Vista/Server 2008,

Mac OS X Version 10.2.8 or later

Emulations

PostScript®3™¹

PCL 6/5c

Fonts

80 outline fonts accessible in all emulations

Print features

Smoothing function, greyscale print, memory saving, duplex print sort function, toner save mode, auto-switch emulation, paper type selection N-up print, password print

Copy functions

Max. original size

A4

Continuous copying

1–99

Zoom range

25–400% in 1% steps

Time to first copy

Approx. 30 seconds or less

Digital features

N-up copy, duplex copy, electronic sort, jam recovery, multiple copy, ID card copy

Image adjustments

Text + photo, text, photo

Scan functions

Functionality

Scan-to-email, scan-to-FTP, scan-to-SMB, TWAIN

Scan speed

Monochrome: 5 seconds or less

Colour: 10 seconds or less

Scan resolution

1,200x1,200 dpi

Max. scan size

A4

Original recognition

Text, photo, text + photo, OCR

Interface

10/100 Base-TX, USB 2.0

Network protocol

TCP/IP, IPP

Operating systems

Windows® 2000/XP/Server 2003/Vista/Server 2008,

Mac OS X Version 10.2.8 or later

File types

TIFF (b/w only), PDF, JPEG (colour only)

Fax functions

Compatibility

ITU-T Super G3

Modem speed

Max. 33.6 kbps

Transmission speed

Less than 4 seconds

Scanning speed

Less than 5 seconds

Scanning resolution

Standard mode: 200 x 100 dpi

Fine mode: 200 x 200 dpi

Max. original size

A4, folio

Compression method

MMR, MR, MH

Memory reception

Up to 100 pages

Address book

50 entries

Quick dialing

Up to 20

Features

Line monitor, tone transmission, pause, on-hook, fax/tel. selection, fax/tel. auto-switching, TAD, line selection, redial, external phone, sequential broadcast, ECM, manual reception, out-of-paper reception, pc-fax (only send, only windows), transmission information (TTI), page No., reports, one-touch dial, abbreviated dial

Consumables

TK-150K Toner-kit

Toner black for up to 6,500 pages in accordance with ISO/IEC 19798.

TK-150C, TK-150M, TK-150Y Toner-kits

Toner cyan, magenta, yellow for up to 6,000 pages in accordance with ISO/IEC 19798.

Capacity of starter toner is black 1,000 pages, cyan, magenta, yellow 1,000 pages in accordance with ISO/IEC 19798.

Options

Paper handling

PF-110 paper feeder

500 sheets, 60–105 g/m², A4

Memory

1 DIMM slot (256 MB)



Your KYOCERA Business Partner:

KYOCERA MITA Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany

Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100

www.kyoceramita-europe.com – info@kyoceramita-europe.com

KYOCERA MITA Corporation – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku

Osaka 540-8585 – Japan – www.kyoceramita.com

* KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.



Product depicted includes optional extras.

KYOCERA