

FS-C2526MFP/FS-C2626MFP

► print ► copy ► scan ► fax

GET IN TOUCH WITH HIGH COLOUR PRODUCTIVITY.

Speed and reliability in colour and b/w is now combined with even higher usability to fulfill the growing demand of small and medium-sized workgroups. These highly productive devices with their integrated colour touch panel provide direct access to the full potential of the compact A4 MFP. The document workflow can be optimized with the use of dedicated program keys and the integrated solution platform HyPAS. The exceptional reliability of KYOCERA's long-life components makes them ideal for your finances and good for the environment.

- Up to 26 pages per minute in A4 in colour and b/w
- Time to first copy: 10(12) seconds in b/w (colour)
- Double-sided print, copy, scan and fax* functionality as standard
- Powerful controller: 800 MHz, 1 GB RAM, Gigabit interface
- Full-colour touch panel provides ease of use
- High security through SSL, IPsec and Private Print functionality
- HyPAS solution platform enables powerful customizations
- Compact design with low noise
- Exceptionally low printing costs in its class

* Only FS-C2626MFP.

Ease of use is provided by the full-colour touch panel with direct access to frequently used functions, programs and addresses.



Card authentication key helps to control the access and user rights of the device without time-consuming login procedures.



FS-C2526MFP/FS-C2626MFP

COLOUR MULTIFUNCTIONALS FOR A4 FORMAT



ECOSYS stands for ECOlogy,
ECONomy and SYStem-printing.

With their long-life components, ECOSYS devices are designed to maximise durability and minimise the total cost of ownership with regard to maintenance, administration and consumables. The cartridge-free system means that only the toner has to be replaced regularly. The modular design concept allows you to add workflow-enhancing functions as required. Integrated system software provides long-term cross-network compatibility. KYOCERA's long-life components cost you and the environment less.

PRESCRIBE IIC

With the KYOCERA page design and control language PRESCRIBE IIC, even complex graphics, logos and forms (multipart forms) can be created independently on the system and saved and updated in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

The KM NetViewer

The KM NetViewer enables complete monitoring and control of all ECOSYS printers and digital KYOCERA multifunction units from any Windows® PC and thus provides ideal network administration. It also supports the standardised SNMP protocol.

Status Monitor and Command Center

The Status Monitor shows the current printer's condition and gives direct access to the Command Center for the modification of settings that are not contained in the drivers (e.g. network settings, adjustment of sleep mode or blocking of the control panel).

USB Host Interface for USB Flash Memory

Documents can be printed directly from and scanned to a USB Flash Memory (e.g. USB stick) via the USB host interface. The documents stored as PDF, XPS, TIFF or JPEG are selected directly via the printer's control panel. No computer is required.

HyPAS™ – Hybrid Platform for Advanced Solutions

KYOCERA's powerful software development platform enables users to customize the functionality and operations of the MFP to their individual requirements.

General

Technology: KYOCERA ECOSYS, Colour Laser, HyPAS™ solution platform

Control panel display: 4.3 inch full-colour touch panel display

Engine speed: Up to 26 pages A4 per minute in colour and b/w

Resolution: 600 x 600 dpi, multitbit technology for print quality of up to 9,600 x 600 dpi (print), 600 x 600 dpi, 256 greyscales per colour (scan/copy)

Duty cycle: Max. 65,000 pages per month

Warm-up time: Approx. 29 seconds or less

Time to first print: Approx. 9/10.5 seconds or less in b/w/colour

Time to first copy: Approx. 10/12 seconds or less in b/w/colour

CPU: PowerPC 464/800 MHz

Memory: Standard 1,024 MB, max. 2,048 MB

Standard interface: USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10/100/1000Base-TX, slot for optional print server, slot for optional CompactFlash® card

Integrated accounting: 100 department codes

Dimensions (W x D x H): 514 x 550 x 603 mm

Weight: Approx. 38.7 kg including toner container

Power source: AC 220 ~ 240 V, 50/60 Hz

Power consumption

	FS-C2526MFP	FS-C2626MFP
Printing:	468 W	475 W
Copying:	465 W	469 W
Stand-by:	78 W	76 W
Sleep-mode:	14 W	16 W

Noise level (sound pressure level ISO 7779/ISO 9296):

Copying/Printing: 50 dB(A)

Stand-by: 30 dB(A)

Safety standards: TÜV/GS, CE

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

Paper handling

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity: 50-sheet multi-purpose tray, 60-220 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Envelopes, Custom (70 x148 to 216 x 356 mm), 250-sheet universal paper cassette, 60-163 g/m², A4, A5, A6, B5, Letter, Legal, Folio, Custom (105 x 148 to 216 x 356 mm).

Max. input capacity with options: 1,300 sheets

Duplex unit: Duplex as standard supports 60-163 g/m²

Reversing document processor: 50-sheet, simplex scan 50-120 g/m², duplex scan 50-110 g/m², A4, A5, B5, Letter, Legal, Custom (140 x 210 to 216 x 356 mm)

Output capacity: Max. 150 sheets face-down

Your KYOCERA Business Partner:

Print functions

Controller language: PRESCRIBE IIC

Emulations: PCL 6 (5c/XL), KPDL 3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print

Operating systems: All current Windows operating systems, MAC OS X Version 10.4 or higher, Unix, Linux as well as other operating systems on request

Fonts/barcodes: 93 outline fonts (PCL 6, KPDL3) + 8 (Windows Vista), 1 bitmap font, 45 types of one-dimensional barcodes, 1 type of two-dimensional barcode (PDF417)

Features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3 and Private Print

Copy functions

Max. original size: A4/Legal

Continuous copying: 1-999

Zoom range: 25-400% in 1% steps

Pre-set magnification ratios: 7 Reductions / 5 Enlargements

Exposure mode: Auto, manual: 7 steps

Image adjustments: Text, photo, mix, graphic/map, printer output

Features: Scan-once-copy-many, electronic sort, 2in1, 4in1, ID-card copy, job reserve, priority print, program, auto duplex copy, split copy, continuous scan, auto cassette change, copy density control

Scan functions

Functionality: Scan-to-e-mail, Scan-to-FTP, Scan-to-SMB, Scan to USB Host, Network TWAIN, WSD (WIA) scan (USB, network)

Scan speed: 35 ipm (300 dpi, A4, b/w), 25 ipm (600 dpi, A4 b/w, 300 dpi, A4, colour)

Scan resolution: 600, 400, 300, 200 dpi (256 greyscales per colour)

Max. scan size: A4, Legal

Original recognition: Text, photo, text + photo, OCR

File types: TIFF, PDF, PDF/A, JPEG, XPS

Compression method: MMR/JPEG

Features: Integrated address book, Active Directory support, encrypted data transfer, mail send (e-mail, fax, SMB/FTP folder, print) at once

Fax functions (FS-C2626MFP only)

Compatibility: ITU-T Super G3

Modem speed: Max. 33.6 kbps

Transmission speed: Less than 3 seconds

Scanning speed: 2.5 seconds

One-touch dial: 100 numbers

Address book: 200 entries

Scanning density

Normal: 8 dot/mm x 3.85 line/mm

Fine: 8 dot/mm x 7.7 line/mm

Superfine: 8 dot/mm x 15.4 line/mm

Ultrafine: 16 dot/mm x 15.4 line/mm

Halftone: 256 greyscales

Maximum original size: A4, Legal

Compression method: JBIG, MMR, MR, MH

Memory reception: 256 sheets or more

Features: Network fax, duplex transmission and reception, encrypted transmission and reception, polling transmission and reception, broadcast

Options

Paper handling

PF-520 Paper feeder: Max. 500 sheets; 60-163 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm - 216 x 356 mm)

PF-530 Paper feeder: Max. 500 sheets; 60-220 g/m²; A4, A5, B5, Letter, Legal, Custom (148 x 210 mm - 216 x 356 mm)

Memory upgrade: MDDR2-256: 256 MB; MDDR2-512: 512 MB, MDDR2-1024: 1,024 MB

CompactFlash® card: CF-4 (4 GB) for printing forms, fonts, logos, macro storage

USB Flash Memory: Supports direct printing and scanning of PDF, XPS, TIFF, JPEG files via USB Host interface

UG-33: ThinPrint support

USB IC Card Reader + Card Authentication Kit (B): Support for various authentication keys available

IC Card Reader Holder (D): To integrate the USB IC Card Reader

Optional interface

IB-50: Gigabit-Printserver 10BaseT/100BaseTX/1000BaseT

CB-520 Cabinet: Wooden desk with storage capacity, including castors (wheels)

Consumables

Average continuous toner yield in accordance with ISO/IEC 19798

TK-590K Toner-Kit: Microfine toner black for 7,000 pages A4

TK-590C, TK-590M, TK-590Y Toner-Kits: Microfine toner cyan, magenta, yellow for 5,000 pages A4

Capacity of starter toner is black 3,500 pages A4, cyan, magenta, yellow 2,500 pages A4

Warranty

1-year warranty** as standard. KYOCERA guarantees the drum and developer for 3 years or 200,000 pages (whichever occurs sooner), provided each device is used and cleaned in accordance with the service instructions.

KYO LIFE Up to 5-year on-site warranty extensions available for product and options.



HyPAS™



Product depicted includes optional extras.

KYOCERA MITA Europe B.V. – Branch Office Germany – Otto-Hahn-Straße 12 – 40670 Meerbusch – Germany
Tel +49 (0) 2159 928-500 – Fax +49 (0) 2159 918-100
www.kyoceramita-europe.com – info@kyoceramita-europe.com

KYOCERA MITA Corporation – 2-28, 1-Chome – Tamatsukuri – Chuo-Ku
Osaka 540-8585 – Japan – www.kyoceramita.com

*KYOCERA does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

** Depending on the country

KYOCERA