

KM-2560

A3 MULTIFUNCTIONAL

► print ► copy ► scan ► fax

COMFORTABLY HANDLES EVERYONE'S PROJECTS.

The KM-2560 multifunctional easily handles the various projects of a networked workgroup or tightly knit department by allowing simultaneous processing of multiple jobs. Universal design features give everyone in the workgroup equal access to productivity-enhancing technology, regardless of their strength or physical ability.

- Simultaneous multitasking and multi-sending
- 80GB HDD
- 512MB memory standard, upgradeable to 1GB
- 25 pages per minute monochrome printing/copying
- Long-life components for outstanding reliability

Product depicted includes optional extras



Colour touch-panel with intuitive menus and easy-to-view colour thumbnails.

Easy-to-open paper cassettes with ergonomically designed handles.



KM-2560

A3 MULTIFUNCTIONAL

The KM-2560 incorporates extremely durable components that guarantee efficient and reliable operation to meet the demanding requirements of busy office environments. The KM-2560 provides effective productivity and maximises up-time whilst ensuring a minimum impact on the environment.

GENERAL

Technology: Kyocera Laser, Mono component
Engine speed: Max. 25/12.5 pages per minute A4/A3
Resolution: 600 x 600 dpi (copy), 1,800 dpi level x 600 dpi (copy, photo mode), 1,200 dpi quality (print)
Time to first copy: 4.7 seconds or less
Warm-up time: 29 seconds or less from power on
Power source: AC 220 ~ 240 V, 50/60 Hz
Power consumption: Printing: 560 W, Stand-by: 160 W, Power-Saving (ECOpower): 8.7 W
Noise (ISO 7779): Printing/copying: 64.7 dB(A), Stand-by: 47 dB(A), Power-Saving (ECOpower): Immeasurably low
Dimensions (W x D x H): Main unit: 570 x 620 x 767.2 mm
Weight: Main unit: Approx. 75 kg
Certifications: TÜV/GS, CE, ISO 15408 (under evaluation)
This product is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.

PAPER HANDLING

All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by Kyocera under normal environmental conditions.

Input capacity: 2 x 500-sheet universal paper feeder, 60-120g/m², A3-A5R, Folio
200-sheet multi-purpose tray, 45-200g/m², A3-A6R, Folio, envelopes
Max. input capacity with options: 2,200 sheets
Duplex as standard supports A3-A5, 60-80g/m²
Output capacity: 250 sheets face-down

COPY FUNCTIONS

Max. original size: A3
Continuous copying: 1-999
Memory capacity: Standard 512MB (max. 1GB) + 80GB HDD (system shared)
Zoom range: 25-400% in 1% steps (with DP-670: 25-200%)
Preset magnification ratios: 5R / 5E
Digital features: Interrupt output job, scan once print many, electronic sort, rotate sort, rotate copy, N-up copy, split copy, cover mode, page numbering, box image overlay, margin shift, border erase
Exposure mode: Auto, manual: 7 or 13 steps
Image adjustments: Text + photo, text, photo

PRINT FUNCTIONS

Processor: PowerPC 750CXr / 400MHz
Memory: Standard 512MB (max. 1GB) + 80GB HDD (system shared)
Emulations: PCL6 incl. P.J.L, KPDL 3 (PostScript 3 compatible), KC-GL (HP-7550A), PDF direct printing, Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630
Controller language: PRESCRIBE IIe
Fonts: 80 outline fonts (PCL6), 136 PostScript KPDL 3 fonts, 1 bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)
Downloadable fonts: Kyocera, PCL + TrueType format, Type 1 + 3 format
Features: eMPS – for quick copy, proof and hold, private print, job storage and job management functionality

Interfaces

Standard interface: USB 2.0 (Hi-Speed), USB Host Interface dedicated for USB Flash Memory device, Fast Ethernet 10-Base-T/100Base-TX, CF slot
Multiple interface connection (MIC): Allows simultaneous data transfer via up to four interfaces, with each interface having its own virtual printer.

SCAN FUNCTIONS

Functionality: Scan-to-SMB/FTP, scan-to-email, scan-to-BOX, network TWAIN, BOX TWAIN
Scan speed: 50 originals per minute in b/w (300 dpi/A4), 15 originals per minute in colour (300 dpi/A4)
30 originals per minute in b/w (600 dpi/A4), 15 originals per minute in colour (600 dpi/A4)
Scan resolution: 600, 400, 300, 200, 200 x 400, 200 x 100 dpi (256 greyscales, 256 colour)*
Max. scan size: A3
Original recognition: Text, photo, text + photo, OCR
Interface: 10Base-T/100Base-TX
Network protocol: TCP/IP
File types: Mono: TIFF, PDF
Colour: JPEG, PDF, TIFF (JPEG)
Compression format: B/W: G4 (MMR), Colour: JPEG
Bundle software: KM-NET Viewer, TWAIN source

*Colour scanning at resolutions of 400 dpi and above requires additional memory.

FAX FUNCTIONS (OPTIONAL)

Compability: ITU-T Super G3
Modem speed: Max. 33.6 kbps
Transmission speed: 3 seconds or less (JBIG)
Scanning density: Normal: 8 dot/mm x 3.85 line/mm, Fine: 8 dot/mm x 7.7 line/mm, Superfine: 8 dot/mm x 15.4 line/mm, Ultrafine: 16 dot/mm x 15.4 line/mm, 600 x 600 dpi
Max. original size: A3
Compression method: JBIG, MMR, MR, MH
Memory: Standard 120MB (enable fax image back up)
Features: Internet fax, network fax, rotate transmission, confidential, relay and bulletin board transmission delivery to document box

OPTIONS

Fax System (M)

Paper handling
DP-670 Document processor: 75 sheets, 45-160g/m², A3-A5R, Folio (RADF), colour scan
PF-670 Paper feeder: 2 x 500 sheets, 60-120g/m², A3, A4, A4R, A5R, B4, B5, B5R, Letter, Letter-R, Legal, Ledger, Folio, STMT

DF-670 Document finisher: Max. 500 sheets A4 or 250 sheets A3, Folio, 60-105g/m², one position stapling max. 30 sheets A4 or 20 sheets A3
DF-730 Document finisher + AK-670*: Max. 1,000 sheets A4 or 500 sheets A3/B4, 64-128g/m², A3-B5, one position stapling max. 30 sheets A4 or 20 sheets A3/B4, 64-128g/m²
JS-670 Job separator: 100 sheets internal job separator, 45-160 g/m², A3-A5R

*Adapter-Kit AK-670 is required for the use of DF-730 document finisher.

Memory

DIMM memory: 512MB memory, DDR SDRAM DIMM (100 pin): 2 slots (1 slot empty), max. 1GB
CompactFlash® card: 1 slot (up to 4GB) for forms, fonts, logos, macro storage
BU-10 Back up memory: 128MB for fax box image back up

Security

Data security kit (C)
UG-30: PDF expansion kit (high-compression, encryption file)

Optional interface for print functions

SB-70 Network card: Wireless LAN – IEEE 802.11b
SB-110FX Network card: 10Base-T/100Base-TX/100Base-FX, FibreOptic
SB-110 Network card: 10Base-T/100Base-TX

Others

Platen cover (D)
CB-670 Cabinet: Wooden desk with storage capacity
CB-671 Cabinet: Metal desk with storage capacity

CONSUMABLES

TK-675 Toner-kit: Microfine toner for 20,000 pages with 6% coverage



Select your options to suit your needs:



Product depicted includes optional extras

Your Kyocera Business Partner:

KYOCERA MITA Europe B.V., Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands, Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com, info@kyoceramita-europe.com

KYOCERA MITA Corporation, 2-28, 1-Chome, Tamatsukuri, Chuo-Ku, Osaka 540-8585, Japan, www.kyoceramita.com

Kyocera does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

KYOCERA